

Base Window Configuration			Requirements for IECC Climate Zones 1-8											
			Base Window with CLEAR Storm Glass		1		2		3		4		5 to 8	
			U-FACTOR	SHGC	U-FACTOR	SHGC	U-FACTOR	SHGC	U-FACTOR	SHGC	U-FACTOR	SHGC	U-FACTOR	SHGC
<b>Wood</b>	Single Glazed	Clear	0.45	0.62	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Clear	0.30	0.56	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e	0.25	0.52	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e Argon	0.25	0.52	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
<b>Aluminum Clad Wood</b>	Single Glazed	Clear	0.47	0.62	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Clear	0.34	0.56	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e	0.29	0.49	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e Argon	0.28	0.49	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
<b>Aluminum</b>	Single Glazed	Clear	0.63	0.62	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Clear	0.47	0.56	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e	0.42	0.52	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e Argon	0.42	0.52	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
<b>Vinyl</b>	Single Glazed	Clear	0.47	0.62	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Clear	0.32	0.56	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e	0.26	0.49	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e Argon	0.25	0.49	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-

Compare base window with storm configuration to your climate zone to determine if it meets the requirements for the International Energy Conservation Code ® (IECC)

Base Window Configuration			Requirements for IECC Climate Zones 1-8											
			Base Window with LOW-E Storm Glass		1		2		3		4		5 to 8	
			U-FACTOR	SHGC	U-FACTOR	SHGC	U-FACTOR	SHGC	U-FACTOR	SHGC	U-FACTOR	SHGC	U-FACTOR	SHGC
<b>Wood</b>	Single Glazed	Clear	0.35	0.54	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Clear	0.25	0.49	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e	0.21	0.46	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e Argon	0.21	0.45	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
<b>Aluminum Clad Wood</b>	Single Glazed	Clear	0.39	0.54	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Clear	0.30	0.49	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e	0.26	0.46	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e Argon	0.25	0.45	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
<b>Aluminum</b>	Single Glazed	Clear	0.53	0.54	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Clear	0.42	0.49	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e	0.38	0.46	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e Argon	0.37	0.45	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
<b>Vinyl</b>	Single Glazed	Clear	0.38	0.54	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Clear	0.27	0.49	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e	0.23	0.46	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-
	Dual Glazed	Low-e Argon	0.22	0.45	1.2	0.4	0.75	0.4	0.65	0.4	0.4	-	0.35	-

Compare base window with storm configuration to your climate zone to determine if it meets the requirements for the International Energy Conservation Code ® (IECC)